

CLAIM AMENDMENTS:

Claims 1 through 16 cancelled.

17. (new) A toilet structure comprising:

a first toilet cubicle having a first toilet, a first access opening, and a first door for closing said first access opening;

a second toilet cubicle adjacent to said first toilet cubicle, said second toilet cubicle having a second toilet, a second access opening, and a second door for closing said second access opening; and

a separating wall disposed between said first toilet cubicle and said second toilet cubicle, said separating wall having a separation position in which said first toilet cubicle is separated from said second toilet cubicle, said separating wall also having a release position in which said first toilet cubicle and said second toilet cubicle are combined into one common toilet space, wherein said first access opening is directly adjacent to said second access opening, said first and said second access openings combining to form one enlarged common access opening in said release position of said separating wall.

18. (new) The toilet structure of claim 17, wherein said separating wall comprises several vertical, adjacent wall elements which can each be pivoted about a vertical axis.

19. (new) The toilet structure of claim 18, wherein said wall elements are connected to each other in a hinged manner.
20. (new) The toilet structure of claim 18, wherein said wall elements are stacked against each other in said release position.
21. (new) The toilet structure of claim 18, wherein said wall elements abut a side wall of said common toilet space in said release position.
22. (new) The toilet structure of claim 17, wherein said the separating wall is formed from several horizontal wall elements which are disposed on top of each other and can each be pivoted about a horizontal axis.
23. (new) The toilet structure of claim 22, wherein said wall elements are connected to each other in a hinged manner.
24. (new) The toilet structure of claim 22, wherein said wall elements are stacked against each other in said release position.
25. (new) The toilet structure of claim 22, wherein said wall elements are disposed in a ceiling region of said common toilet space in said release position.
26. (new) The toilet structure of claim 22, wherein adjacent wall elements are in mutual engagement in said separating position of said separating wall.

27. (new) The toilet structure of claim 17, wherein said separating wall can be displaced in its entirety substantially in a plane of said separating wall.
28. (new) The toilet structure of claim 27, wherein said separating wall is disposed outside of said common toilet space in said release position.
29. (new) The toilet structure of claim 28, wherein said separating wall comprises a plurality of vertical, adjacent panels which can be deflected through approximately 90° at an outer side of said common toilet space.
30. (new) The toilet structure of claim 28, wherein said separating wall comprises a plurality of vertical, adjacent panels which can be wound onto a winding mandrel at an outer side of said common toilet space.
31. (new) A toilet structure comprising:
 - a first toilet cubicle having a first toilet, a first access opening, and a first door for closing said first access opening;
 - a second toilet cubicle adjacent to said first toilet cubicle, said second toilet cubicle having a second toilet, a second access opening, and a second door for closing said second access opening; and
 - a separating wall disposed between said first toilet cubicle and said second toilet cubicle, said separating wall having a first position in which said first toilet cubicle is separated from said second toilet cubicle, said separating wall also

having a second position displaced substantially perpendicularly to a plane of said separating wall in said first position such that said first toilet cubicle is enlarged and said second toilet cubicle is reduced in size, wherein said first access opening is directly adjacent to said second access opening, said first and said second access openings combining to form one enlarged common access opening in said second position of said separating wall.

32. (new) The toilet structure of claim 31, wherein said separating wall can be displaced in opposite directions.